

**Product Data** 

# **Castrol Transmax Dex/Merc**

Automatic Transmission Fluid

## **Description**

Castrol Transmax<sup>™</sup> DEX/MERC Domestic Multi-Vehicle Transmission Fluid is for use in older Ford and General Motors vehicles.

## **Advantages**

- Enhanced friction durability for smooth transmission performance
- Meets DEXRON®-IIIH requirements. Also satisfies requirements of DEXRON®, DEXRON®-III, IIE and II. Do not
  use this ATF in applications calling for DEXRON®-VI. Use Castrol Transmax™ Type F ATF in applications calling
  for Type F.
- Meets MERCON® requirements. May also be used in power steering applications where MERCON® is required. Do not use this ATF in applications calling for MERCON® V or MERCON® SP.

## **Warranty and Protection Requirements**

Exceeds all passenger car and light truck manufacturer's warranty requirements for vehicles, transmissions or power steering service where a DEXRON®-IIIH or MERCON® type ATF is specified

#### **Industry Specifications and OEM Approvals**

Meets or Exceeds General Motors DEXRON®-IIIH Requirements

• Meets or Exceeds Ford MERCON® Requirements

# **Typical Characteristics**

| Test                              | Method      | Typical Results |
|-----------------------------------|-------------|-----------------|
| Viscosity at 40°C, cSt            | ASTM D-445  | 32              |
| Viscosity at 100°C, cSt           | ASTM D-445  | 7.2             |
| Viscosity Index                   | ASTM D-2270 | 200             |
| Color, Typical                    | ASTM D-1500 | 7               |
| Appearance                        |             | Red             |
| Brookfield Viscosity at -40 C, cP | ASTM D-2983 | 17,000          |
| Pour Point, °C (°F)               | ASTM D-97   | -43(-45)        |
| Flash Point, °C (°F)              | ASTM D-92   | 177(350)        |
| Specific Gravity, 60°F            | ASTM D-1298 | 0.863           |
| Pounds per Gallon                 | ASTM D-287  | 7.19            |

# **Typical Physical Characteristics**

| Test                              | Method      | Typical Results |
|-----------------------------------|-------------|-----------------|
| Viscosity at 40°C, cSt            | ASTM D-445  | 32              |
| Viscosity at 100°C, cSt           | ASTM D-445  | 7.2             |
| Viscosity Index                   | ASTM D-2270 | 200             |
| Color, Typical                    | ASTM D-1500 | 7               |
| Appearance                        |             | Red             |
| Brookfield Viscosity at -40 C, cP | ASTM D-2983 | 17,000          |
| Pour Point, °C (°F)               | ASTM D-97   | -43(-45)        |
| Flash Point, °C (°F)              | ASTM D-92   | 177(350)        |
| Specific Gravity, 60°F            | ASTM D-1298 | 0.863           |
| Pounds per Gallon                 | ASTM D-287  | 7.19            |

## **Product Performance Claims**

Meets Ford Mercon GM - Dexron IIIH

### **Additional Information**

**Part Numbers and UPCs** 

#### **Packaged Goods**

| Case Size        | 6/1 QT          | 3/1 GA          |
|------------------|-----------------|-----------------|
| Case Part No.    | 06820           | 03520           |
| Bottle/ Unit UPC | 0-79191-00462-3 | 0-79191-33520-8 |
| Case UPC         | 0-79191-06820-5 | 0-79191-03520-7 |

#### Bulk/Drum

| Unit Size | 16 GA KEG | 55 GA DRUM | BULK |
|-----------|-----------|------------|------|
| Part No.  | 0463      | 0464       | 0460 |

Castrol Transmax Dex/Merc

12 Mar 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com